


Technical Specification

BACKHOE LOADER



S.N.	CRITERIA	REQUIREMENT	REMARKS
1	General	All wheel drive rigid frame backhoe loader with steel suitable for operation under rough working conditions and adverse climatic condition at operating altitude of 2000 meters and in ambient temperature varying between -5 to 50° Centigrade.	Make: Model: 2013 Country of Origin:
	Capacity	1. Loader: General purpose bucket with bolt on teeth of SEA rated capacity nominally heaped approx. 1Cu.m. with breakout force not less than 6000 kgf.	
		2. Backhoe bucket with excavator type side locking tooth point of SEArated capacity nominally heaped not less than 0.24 cu.m. with breakout force not less than 5700 kgf. and following working ranges:	
		a) Maximum digging	
		height: ≥ 5200 mm	
		b) Maximum digging	
		depth: ≥ 4700 mm	
		c) Maximum digging	
		reach: ≥ 5500 mm	
2	Engine	Four Stroke, Four Cylinder water-cooled, Turbo charged with inter cooler, Four wheel drive, diesel engine, and rated engine power not less than 92 HP 35 to 92 HP 200	
3	Gauges	To include water temperature, fuel: oil pressure, transmission	
4	Power Mode	Atleast two working modes	
5	Transmission	Powershift type range selector	
6	Axles	Four wheel drive with fixed rear axle and not less than 15° oscillation front axles.	
7	Tires	Suitable Four tires with tubes for operating machines in rough road conditions shall be provided.	
8	Steering	Power/ Power assisted	
9	Brakes	Hydraulically actuated, wet multiple disc/caliper disc type service brake and saperate parking brake.	
10	Cab	All steel enclosed cab with laminated glass windscreen insulated roof, suitably located controls for backhoe and loader operation, rare view mirror, cabin light, wiper and adjustable cushioned seat for operator shall be provided.	

10	Hydraulics	Suitable hydraulic pumps and system for smooth operation of all attachment smoothly.	
11	Hydraulics flow	Suitable hydraulic pumps and system for smooth operation of all attachment smoothly and flow <i>not less than 117 lpm.</i>	
12	Essential Accessories	1. Road light, work lights, cabin lights, Fan and F.M Radio 2. Service Hour meter	
13	Instructions	All signs and instructions in equipment shall be in English	
14	Manuals	One copy of the Operator's / owner's instructions and Two copies of following manuals in English shall be supplied a. Spare Parts Catalogue b. Operator manuals	
15	Tools	A set of tools as required for general maintenance	
16	Color	Standard color.	
17	Proven Performance	1. The equipment offered shall be a current model under standard production by the manufacturer. 2. The bidder shall provide the manufacturer's data of performance of the unit to include the <i>fuel consumption, performance curves of the engine and production capacity of the unit.</i>	
18	Warranty	Manufacturer shall provide warranty for minimum of one year or 2000HR whichever is earlier after acceptance.	
19	Delivery	The BACKHOE LOADER 1 (ONE) UNIT, with all the necessary filters and spare parts required for the first one services, shall be delivered to:	
20			



[Signature]
कार्यालय प्रमुख
(स.ई.)